




	XL	BRW-2	BW
			
Types:	XL72, XL96, XL144, XL192	BRW-2	BW144, BW192
Panel cutout according to DIN:	Q72, Q96, Q144, Q192	–	–
Pointer deflection:	180°, 240°, 300°, 360°	180°, 240°, 300°, 360°	180°, 240°, 300°, 360°
Protection IP52/IP54:	IP52	–	–
Protection IP66:	On request	✓	✓
Built-in dimmer:	–	✓	✓
Long life LED illumin.:	✓	✓	✓
Accuracy class:	0.5	0.5	0.5
Scale base colour:	White or black	White or black	White or black
Figures, div. lines:	Black, yellow, red, green, etc.	Black, yellow, red, green, etc.	Black, yellow, red, green, etc.
Pointer:	Yellow illuminated or black shadow	Yellow illuminated or black shadow	Yellow illuminated or black shadow
Interface:	Analogue or CANopen	Analogue or CANopen	Analogue or CANopen
Type approved by:	MED	MED	MED
	Panorama Rudder Indicator	Rudder Angle Transmitter	
			
Types:	TRI-2 (Ø370)	RT-2	
Panel cutout according to DIN:	–	–	
Pointer deflection:	3 × 90°	0...90°, 0...140°	
Protection IP52/IP54:	IP54	–	
Protection IP66:	–	IP66	
Built-in dimmer:	✓	–	
Long life LED illumin.:	✓	–	
Accuracy class:	1.5/1.0	0.5	
Scale base colour:	White or black	–	
Figures, div. lines:	Black, yellow, red, green, etc.	–	
Pointer:	Black or yellow	–	
Interface:	Analogue or CAN	0...20 mA or 4...20 mA	
Type approved by:	MED, CCS, GOST-R	CCS, GL, GOST-R	

