

Type:	TAC-321DG Current transducer for DIN rail or base mounting
-------	------------------------------------------------------------

Technical specifications

Measuring range:	0...100% I_{nom} (standard)
Measuring frequency:	45...65Hz (300...500Hz)
Measuring current:	0-1A AC ($\leq 2,0VA$) 0-5A AC ($\leq 2,3VA$)
Output: (0...100%)	0...10mA / 0...20mA Span adjustment $\pm 20\%$
Auxiliary supply:	No separate auxiliary supply
Accuracy:	Class 0.5 (-10...15...30...55°C) IEC 688 and EN 60688

Type test specifications

Type test specifications		Tested according to:
Insulation:	500V DC, >100M Ω	DNV, GL and LR
Vibration:	3...13.2Hz: 3 mm	Class A, DNV Test 1, GL and LR
	13.2-100Hz: 1.0 g	
Shock:	6 attempts with 15 g (in 3 directions)	IEC 68-2-27, test: Ea
Climate:	Class HSE	DIN 40040
Protection:	Case: IP40	IEC/EN 60529
	Terminals: IP20	
Temperature:	-10...55°C (nominal)	DNV, GL and LR
	-25...70°C (operating)	
	-40...70°C (storage)	
Temperature drift:	Typ. 0.15% per 10°C Max. 0.2% per 10°C	IEC/EN 60688
Galvanic separation:	2kV – 50Hz – 1 min. All circuits mutually	EN 61010-1
EMC:	Immunity	SS4361503 – PL 4, IEC 255-4 – class 3 and EN 50082-1/2
	Emission	EN 50081-1/2

DEIF A/S Frisenborgvej 33 DK-7800 Skive Denmark	Date: 010220	
		Mogens Bentsen Project Manager