

**DEIF A/S****Type certificate**

4124010037A

Type:	VDQ Moving coil
-------	-----------------

**Technical specifications**

Scale:	To DIN 43802	
Measuring range	25...600V, 1...600mA	
VDQ.. Voltmeters 25...600V:	R: approx 1kΩ/V. Range<50V AC: scale non-linear	
VDQ.. Ammeters 1...600mA:	Voltage drop: approx. 1.2V	
Accuracy	Class 1.5 (-10...15...30...55°)	To EN 60051

**Type test specifications****Tested according to:**

Vibration:	3-13.2Hz 3mm 13.2-100Hz 1.0g	Class A, DNV Test 1, GL and LR
Shock:	6 attempts with 15g (in 3 directions) 50g/6ms 22g/20ms	IEC68-2-27, Test: EA
Climate	Class HUE	DIN 40040
Protection	Standard Housing: IP52 Terminals: IP20 Option Housing, front: IP54 Housing, rear: IP52 Terminals: IP20	EN 60529
Temperature:	-10...55°C (nominal) -25...60°C (operating) -40...65°C (storage)	EN 60051 and IEC 51
Safety:	600V CAT. III pollution deg. 2	EN 61010-1
EMC:	Immunity Emission	EN 50082-1/2 EN 50081-1/2

DEIF A/S  
Frisenborgvej 33  
DK-7800 Skive  
Denmark

Date: 010813

*Flemming Hedegaard*  
Flemming Hedegaard  
Supporter

DEIF A/S  
Frisenborgvej 33, DK-7800 Skive, Denmark

Tel: (+45) 9614 9614 • Fax: (+45) 9614 9615  
http://www.deif.com E-mail: deif@deif.com